

MANUFACTURE OF SEMICONDUCTOR DEVICE

Patent Number: JP10256240
Publication date: 1998-09-25
Inventor(s): FUKAZAWA MASANAGA;; KADOMURA SHINGO;; FUKUDA
Applicant(s): SONY CORP
Requested Patent: ☐ JP10256240
Application JP19970158570 19970616
Priority Number(s):
IPC Classification: H01L21/3065; H01L21/768
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To form a connection hole in an interlayer insulating film by a dry etching process, using not only a general composition etching gas but also an etching gas containing no fluorocarbon-loosed gas.

SOLUTION: This method for manufacturing a semiconductor device includes a step of forming a connection hole 14 in an inter-layer insulating film by a dry etching process using an etching gas. In this case, a film 12 having a low dielectric constant is an insulating film which is made of a compound, having SiF or CF couplings in a chemical structural formula. Specifically, the compound may be SiOF, cyclic fluororesin siloxane copolymer or polyfluoroaryl ether. When such an insulating film employed, active species of F- or fluoroacarbon- boased molecules emitted from inside of the connection hole 24 of the inter-layer insulating film can cause an etching rate of the insulating film inside the hole 14 to be increased.

Data supplied from the esp@cenet database - 12

*** NOTICES ***

Japan Patent Office is not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. **** shows the word which can not be translated.
3. In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1] the layer insulation film which consists of a compound which has SiF combination or CF combination in a chemical structure formula by the dry etching using etching gas -- connection -- the manufacture method of the semiconductor device characterized by having the process which forms a hole

[Claim 2] The compound which has SiF combination or CF combination in a chemical structure formula is the manufacture method of the semiconductor device according to claim 1 characterized by the ranges of specific inductive capacity being 1-4.

[Claim 3] the compound which has SiF combination or CF combination in a chemical structure formula -- under etching -- connection of a layer insulation film -- a hole -- the active species of the molecule of F emitted from inside, or a fluorocarbon system -- connection -- a hole -- the manufacture method of the semiconductor device according to claim 1 characterized by including F beyond the grade which can be made to accelerate etching of an inner insulator layer

* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. **** shows the word which can not be translated.
3. In the drawings, any words are not translated.

DESCRIPTION OF DRAWINGS

[Brief Description of the Drawings]

[Drawing 1] the connection formed in the layer insulation film according to the example of this invention -- it is the outline cross section showing a hole

[Drawing 2] It is the outline cross section showing the structure of the sample used for the example of this invention.

[Drawing 3] the connection which tried to form in the layer insulation film used for comparison with the example of this invention -- it is the outline cross section showing a hole

[Description of Notations]

10 Si Substrate and 11 SiO₂ Layer and 12 Low Dielectric Constant Film and 13 Photoresist and 14 Connection -- Hole

[Translation done.]


NOTICES

Japan Patent Office is not responsible for any damages caused by the use of this translation.


1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. **** shows the word which can not be translated.
3. In the drawings, any words are not translated.

DRAWINGS


[Drawing 2]



[Drawing 1]



[Drawing 3]



[Translation done.]